

# DAIRY EFFLUENT SPECIFICATIONS

TANK CAPACITY (1m <sup>3</sup> = 1,000L)	DIMENSIONS	STIRRING VALVES	EMPTY WEIGHT
100m <sup>3</sup>	12.10m x 07.40m	4	261 kg
200m <sup>3</sup>	13.60m x 11.84m	4	469 kg
300m <sup>3</sup>	17.40m x 13.30m	4	675 kg
400m <sup>3</sup>	22.70m x 13.32m	4	871 kg
500m <sup>3</sup>	22.70m x 16.28m	8	1065 kg
600m <sup>3</sup>	24.60m x 17.76m	8	1259 kg
700m <sup>3</sup>	26.20m x 19.24m	8	1450 kg
800m <sup>3</sup>	29.70m x 19.24m	8	1643 kg
900m <sup>3</sup>	30.80m x 20.72m	10	1832 kg
1000m <sup>3</sup>	34.10m x 20.72m	10	2026 kg

## EQUIPMENT INCLUDED:

- 1 x visual measuring device (maximum height 1.6m)
  - 1 x erosion protection layer for your platform
  - 1 x 50mm flexible hose
  - 1 x 50mm effluent spec non-return inlet valve
  - 1 x 100mm anti-vortex outlet with gate valve
- Quick connect 100mm stirring valves with camlocks for effective stirring.

Call Andre to discuss your Flexi Tank: 027 706 3633  
[www.flexitanksnz.com](http://www.flexitanksnz.com) or [info@flexitanksnz.com](mailto:info@flexitanksnz.com)