

INDUSTRIAL LIQUID SPECIFICATIONS

TANK CAPACITY (1m ³ = 1,000L)	DIMENSIONS	STIRRING VALVES	EMPTY WEIGHT
100m ³	12.10m x 07.40m	4	261 kg
200m ³	13.60m x 11.84m	4	469 kg
300m ³	17.40m x 13.30m	4	675 kg
400m ³	22.70m x 13.32m	4	871 kg
500m ³	22.70m x 16.28m	8	1065 kg
600m ³	24.60m x 17.76m	8	1259 kg
700m ³	26.20m x 19.24m	8	1450 kg
800m ³	29.70m x 19.24m	8	1643 kg
900m ³	30.80m x 20.72m	10	1832 kg
1000m ³	34.10m x 20.72m	10	2026 kg

EQUIPMENT INCLUDED:

- 1 x visual measuring device (maximum height 1.6m)
 - 1 x erosion protection layer for your platform
 - 1 x 50mm flexible hose
 - 1 x 50mm effluent spec non-return inlet valve
 - 1 x 100mm anti-vortex outlet with gate valve
- Quick connect 100mm stirring valves with camlocks for effective stirring.

Call Andre to discuss your Flexi Tank: 027 706 3633
www.flexitanksnz.com or info@flexitanksnz.com

